

Hoses

Geoflex Exhaust HT650

GeoFlex Exhaust HT650 is a high temperature hose designed for extraction or air supply of hot air, fumes, smoke or dust within the industry. Suitable for extraction of exhaust gasses from big combines or excavator etc., or extraction of air from a heater.

Material

2 ply, PU- coated high temperature fabric, reinforced by woven in stainless steel wire.

Colour

Silver-grey

Length

1-10 meter

Special-length after request

Temperature resistance

- 60° C to + 600° C,
(interm. up to + 700°C).

Application

Suction of exhaust gases, flue gas extraction and suction of other hot fumes, gases or dust in all fields of industry.



Properties

Good temperature resistance, outer wear strip, flame retardant, silicone free, excellent axial compressibility

Technical specifications

Art. No.	Ø (mm)	Vacuum Pa.	Bend. Rad. (mm)	Weight (kg/m)
09-159 GeoFlex Exhaust HT	102	15000	53	2,100
09-161 GeoFlex Exhaust HT	127	10000	63	2,600
09-163 GeoFlex Exhaust HT	152	6000	73	2,110
09-164 GeoFlex Exhaust HT	160	5500	77	2,250
09-165 GeoFlex Exhaust HT	200	4000	93	2,790
09-166 GeoFlex Exhaust HT	250	3000	115	3,530
09-169 GeoFlex Exhaust HT	315	2000	139	4,350