

## Hose to ventilation

# GeoFlex Weld

GeoFlex Weld for extraction of welding fumes, vapors, ventilation of tanks etc. The hose is very suitable for use together with our extraction arms or portable fan PM-180-1.

### Material

PVC coated polyester fabric

### Colour

Black

### Length

2, 3, 4, 5 or 10 m.

Special length after request

### Temperature resistance

- 10 °C til + 60 °C ( short 110 °C. )

### Application

Air-conditioning,

Extraction of air and welding fumes

### Properties

Light weight

Very flexible

Flame retardant according to NF P 92-503 M2



GeoFlex Weld

### Technical specifications

Art. No	Diam. (mm)	Weight (kg/m)	Bend. Rad. (mm)	Max. over-pressure (kPa)	Max. Vacuum (kPa)
09-301	40	0,10	23	25,0	15,0
09-302	50	0,12	29	24,0	14,5
09-303	63	0,15	36	18,5	10,5
09-306*	80	0,19	43	15,0	7,0
09-307*	102	0,24	54	12,0	5,0
09-310*	127	0,32	67	10,0	3,5
09-312	152	0,37	79	8,0	3,5
09-313*	165	0,46	86	7,5	2,5
09-314*	200	0,60	105	6,0	2,0
09-315	250	0,77	129	5,0	1,0
09-316A*	315	0,96	162	4,0	0,5
09-317	350	1,09	179	3,5	0,5
09-318	400	1,26	204	3,0	0,5
09-320	500	1,54	256	2,0	0,5

\* = Stock items

### Pressure drop

