

Automatic

AirBox Lite

AirBox Lite is an efficient pressure monitor/system monitor that monitors process ventilation systems and sounds an alarm if the pressure falls below the set level according to the Danish Working Environment Authority. The Danish Working Environment Authority's requirements.

AirBox Lite has a built-in pressure switch that is available in three pressure ranges:

• 20 - 300 Pa

• 100 - 1000 Pa

• 500 - 2000 Pa

Protection class: IP22

AirBox Lite meets the Danish Working Environment Authority's minimum requirements and is a competitive alternative to AirBox III. If you want more functionality, AirBox III is recommended.

Airbox Lite is easy to install.

Airbox Lite has a green operation lamp that lights up during normal operation. If the pressure in the extraction system drops below the set alarm point, the red alarm light is activated.

If you want to monitor more than one room or want to connect an external siren or lamp, AirBox III is recommended.



AirBox Lite - Pressure Guard/System Guard: 20-300Pa, 100-1000 Pa and 500-2000 Pa

Ordering table	
Art. No.	Description
13-730	AirBox Lite 500-2000 Pa ventilation guard, monitoring and alarm for process extraction. Easy to install compared to typical ventilation guards and complies with the Danish Working Environment Authority. Red and green control light, no siren.
13-728	AirBox Lite 20-300Pa
13-729	AirBox Lite 100-1000Pa
13-727	AirBox Lite HV 30kPa

Wiring diagram (standard)

